

Product quality	
Formats	914 x 457 x 6,0 mm
Packaging	Pack: 5 elements / 2.088 m <sup>2</sup> / 21.067 kg
	Pallet: 40 packs / 83,540 m <sup>2</sup> / 882,66 kg

Tolerances (Requirement EN 16511:2014)		
Squareness of the elements (≤ 0.20mm)	≤ 0,15 mm	
Determination of Linearity (≤ 0.30 mm/m)	≤ 0,20 mm/m	
Flatness concave / convex	lengthwise (≤ 0.50/≤ 1.0 %)	≤ 0,30/≤ 0,50 %
	wide (≤ 0.15/≤ 0.20 %)	≤ 0,10/≤ 0,15 %
Surface flushness	(average ≤ 0.10 mm)	(average ≤ 0.10 mm)
	(max. ≤ 0.15 mm)	(max. ≤ 0.15 mm)
Opening between installed elements	(average ≤ 0.15 mm)	(average ≤ 0,05 mm)
	(max. ≤ 0.20 mm)	(max. ≤ 0.10 mm)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (see notes in our advisor)
Lifetime	10 years	- cleaning an maintenance see instructions
		- technical changes reserved



EN 14041:2004/AC:2006



Quality  
Production  
Controlled  
Functionality



www.tuv.com  
ID 000005715

Classification		Test method	Rating
<b>Utility class 23</b> domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office	
<b>Utility class 33</b> commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops	
Wear layer	ISO 24340	0,55 mm	
Surface Coating		PUR	
Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1	
Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS	
Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change	
Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6	
Resistance to roller castor chairs	EN 425	Type W, no visible changes	
<b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,029 m <sup>2</sup> *K/W	
Moving a furniture leg	EN 424	No visible changes	
Indentation-residual	EN ISO 24343-1	≤ 0,10 mm	
Acoustical - Impact noise reduction	EN ISO 10140	17 dB	
Length- and Square separating force	ISO 24334	lengthwise ≥ 4 KN/m transversely ≥ 3 KN/m	
Abrasion	prEN 15468 Annex A	> 5.000 rev.	
Dimensional stability	EN ISO 23999	≤ 0,20 %	
Micro scratch resistance	EN 16094	Method A MSR-A1	
Antimicrobial activity	ISO 22196	Antibacterial	
Slip resistance on an inclined plane	DIN 51130	Mineral texture: R9	
Disposal	EAK-Code-number	20 01 39	
Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).			

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Trendtime-5_EN_20210801
Date:	15.12.2018	Latest update at:	<a href="https://parador.de/en/partner/downloads/index/cat/11/">https://parador.de/en/partner/downloads/index/cat/11/</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.08.2021